



# Glu-All<sup>®</sup>

## Radio Frequency Hydraulic Edge Gluing Press



**L&L MACHINERY, INC.**

- Welded AND bolted one-inch thick milled steel jaw.
- Only RF edge gluer with L&L's patented Vertical Pusher Shoes.
- No downtime to change product thickness.
- Standard PLC controls.
- Auto-Start feature.
- Ultra-fast edge-gluing or face-gluing production.
- Numerous options available (*see reverse for details*).

# GLU-ALL® RF EDGE GLUING PRESSES

## Hydraulic Pressure Standard Configurations

Model	Gluing Capacity	kW Power	In-Feed*	Optional Out-feed*
GA-43	26"x43"x4.5"	6	33"x73"	33"x49"
GA-60	40"x60"x4.5"	10	47"x97" (opt.)	47"x67"
GA-84	40"x84"x4.5"	15	47"x123"	47"x91"
GA-100	50"x100"x4.5"	20	60"x140"	60"x109"
	50"x120"x4.5"	30	60"x160"	60"x129"
	50"x144"x4.5"	50	60"x184"	60"x153"
GA-100				
SLAT BED	36"x100"x4.5"	30	38"x109"	51"x109"
	50"x100"x4.5"	50	60"x122"	60"x122"

*Note: Specific platen dimensions can be ordered within each model designation.*

*Generator capacities should be matched with production requirements (100 sq. in./kW of glueline/minute).*

*\*Gross outside dimensions*

## Options

Outfeed Steel Table  
 Outfeed Dead Roll Table  
 Auto-Tune Gluing System  
 Auto-Indexing Infeed System  
 6.5" Thickness Double Row Edge Cylinders  
 8.5" Thickness Double Row Edge Cylinders  
 11" Thickness Triple Row Edge Cylinders  
 Extra Platen Length  
 Lift-up End Pressure



**L&L MACHINERY, INC.** manufacturing high quality woodworking machinery since 1959

5901 W. Hwy. 22 • Crestwood, KY 40014 • 502-241-1502 • fax 502-241-5907

sales@LandLMachinery.com • www.LandLMachinery.com